



# SUBMITTAL: HUBLESS CAST IRON SOIL PIPE & FITTINGS

Welcome to the NewAge

12630 West Airport Blvd., Suite 100 • Sugar Land, Texas 77478 • Phone: 281.565.0928 • Fax: 281.565.0929 • Toll Free: 1-866.791.7055 • E-Mail: info@newagecasting.com

Date: \_\_\_\_\_ Engineer: \_\_\_\_\_ Job Name: \_\_\_\_\_

Contractor: \_\_\_\_\_ Location: \_\_\_\_\_

## HUBLESS PIPE & FITTINGS

### Standards & Certifications


Hubless cast iron soil pipe and fittings utilized in drain, waste and vent (DWV) and sewer and storm drainage lines. This system is intended to be used in non-pressurized, gravity-based applications.

All hubless cast iron soil pipe and fittings shall be third party accredited and certified to comply with standard of the most recent version of ASTM A 888 and CISPI 301 including Annex A1. All pipe and fittings shall bare the marking requirements of ASTM A 888 and CISPI 301.


		LISTED AND CERTIFIED BY:		
STANDARDS	ASTM A888	X	X	X
	CISPI 301	X	X	X

Product installation shall conform to the standard industry practices, and all applicable plumbing, fire and building code requirements. Following installation, it is recommended that the system be hydrostatically tested to ten feet of head or 4.3 PSI.


HUBLESS PIPE 10 FOOT LAYING LENGTH				
NOMINAL SIZE	B INSIDE DIAMETER	J OUTSIDE DIAMETER	T	
			NOM.	MIN.
1-1/2	1.50 ± 0.09	1.90 ± 0.06	0.16	0.13
2	1.96 ± 0.09	2.35 ± 0.09	0.16	0.13
3	2.96 ± 0.09	3.35 ± 0.09	0.16	0.13
4	3.94 ± 0.09	4.38 ± 0.09	0.19	0.15
5	4.94 ± 0.09	5.30 ± .09 - .05	0.19	0.15
6	5.94 ± 0.09	6.30 ± .09 - .05	0.19	0.15
8	7.94 ± 0.13	8.38 ± .09 - .05	0.23	0.17
10	10.00 ± 0.13	10.56 ± 0.09	0.28	0.22
12	11.94 ± 0.13	12.50 ± 0.13	0.28	0.22
15	15.11 ± 0.13	15.83 ± 0.13	0.36	0.30




Quarter Bend




Wye




P-Trap



Double Quarter Bend



San Cross



Double Combination Wye

